Product Safety Data S	XEROX	,	
Product: DocuPrint 377CF DocuPrint 420CFT		PSDS No.: 0782 ISSUE DATE: 05/06/96 REV. DATE: 08/30/00	
Section I - Product Identific	ation	REV. DATE. 00/30/00	
Manufacturer's Name Xerox Corporation		Emergency No.EH&S Inquiries(585) 422-2177(800) 828-6571	
Manufacturer's A El Segundo, Calif			
Product Designation DocuPrint 377CF DocuPrint 420CFT		Product Code NDZ 2240	
Section II - Electrical Inform Line Voltage (Volts) 208	Line Current Free (Amps) (He	eq.Branch Cir. Protectionertz)(Amps)6060	
Line Cord / Plug Specification 3 Phases + Ground		Power Consumption** (Watts) 21 KVA	
Agency Approva UL File Number E CSA File Number	160856		
Section III - Supplies Toner Developer Fuser	Xerox Part No. 6R852 5R592 8R2955	Material Safety Data Sheet A-02094 B-0301 D-0407	
Section IV - Environmental Product Size IOT (Centimeters) W: 94 L:206		Environmental Limitations <u>Min Max</u> Relative Humidity (%) 20 75 Ambient Temp. (°C) 15 30	

H: 153

PRODUCT: DocuPrint 377CF DocuPrint 420CFT

Floor Space Requirements

(Meters) 1.85 sq Weight (K Grams) 1060

Section V - Emission/Exposure Information*

Light Source: LED Light Emitting Diode - Array

Electromagnetic Emissions

U.S.	FCC: Class	А
Canada	DOC: Class	А

Audible Noise

Run 67db (A)

TLV *** 85 db (A)

*** **TLV** (Threshold Limit Value) Level) is set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. This level is considered maximum exposure permitted to ensure no health hazard.

08/30/00

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.